Datasheet revision 1.0 www.chipquik.com

# Sn95.5/Ag4.0/Cu0.5 Solder Spheres for BGAs

## **Product Highlights**

Chip Quik® BGA solder spheres are manufactured from virgin materials to meet or exceed the requirements of building or repairing BGA packages. Chip Quik® BGA solder spheres also exceed both the IPC and MIL standards for purity levels and size tolerances. Nominal sizes are available from 0.20 to 0.76 mm (8 to 30 mil).

#### **Product Specifications**

| Part Number               | Alloy              | Melting Point | Diameter | Quantity (by weight) |
|---------------------------|--------------------|---------------|----------|----------------------|
| CQ-SS-SAC405-0.20MM-25000 |                    |               | 0.20 mm  | 25,000               |
| CQ-SS-SAC405-0.25MM-25000 |                    |               | 0.25 mm  | 25,000               |
| CQ-SS-SAC405-0.30MM-25000 | Sn95.5/Ag4.0/Cu0.5 | 217°C (423°F) | 0.30 mm  | 25,000               |
| CQ-SS-SAC405-0.35MM-25000 |                    |               | 0.35 mm  | 25,000               |
| CQ-SS-SAC405-0.40MM-25000 |                    |               | 0.40 mm  | 25,000               |
| CQ-SS-SAC405-0.45MM-25000 |                    |               | 0.45 mm  | 25,000               |
| CQ-SS-SAC405-0.50MM-25000 |                    |               | 0.50 mm  | 25,000               |
| CQ-SS-SAC405-0.60MM-25000 |                    |               | 0.60 mm  | 25,000               |
| CQ-SS-SAC405-0.76MM-25000 |                    |               | 0.76 mm  | 25,000               |

Shelf Life: >24 months

#### **Test Results**

| Test J-STD-004 or other requirements as stated | Test Requirement                                      | Result   |
|--|---|--|
| Conflict Minerals Compliance                   | Electronic Industry Citizenship Coalition (EICC)      | Compliant  |
| REACH Compliance                               | Articles 33 and 67 of Regulation (EC)<br>No 1907/2006 | Contains no substance >0.1% w/w that is listed as a SVHC or restricted for use in solder materials |

### **Conforms to the following Industry Standards:**

J-STD-006C, Amendments 1 & 2 (Solder Alloys and Fluxed/Non-Fluxed Solders): Yes RoHS 3 Directive (EU) 2015/863: Yes