CHIPQUIK®

www.chipquik.com

Leaded Solder

Safety Data Sheet (SDS) www.chipquik.co To comply with European CLP Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878, US 29CFR 1910.1200 OSHA's Hazard Communication Standard, and Australian NOHSC: 1008 [2004] and ADG Code 7.4

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SYNONYMS:	Chip Quik Leaded Solder Bar, Ribbon, Solid Core Wire, Solder Shot		
PART NUMBERS:	BARSN60PB40, BARSN63PB37, BARSN62PB36AG2, BARSN60PB40-8OZ, BARSN63PB37-8OZ, BARSN62PB36AG2- 8OZ, SMDPB100-S-1, SMDPB100-S-16, EXB-SN60PB40, EXB-SN63PB37, EXB-SN63PB37-0.5LB, EXB-SN62PB36AG2, SMD-SC-SN60PB40-0.031-1oz, SMD-SC-SN63PB37-0.031-1oz, SMD-SC-SN62PB36AG2-0.031-1oz, EXLB-SN63PB37, EXLB-SN63PB37-20LB, SMD-SC-SN5PB95-0.062-1LB		
MANUFACTURER: ADDRESS:	Chip Quik Inc. 931-3909 Witmer Rd., Niagara Falls, NY 14305 (USA) 3rd Floor, 207 Regent Street, London W1B 3HH (UK) 13 Adelaide Road, Dublin, Ireland, D02 P950 (EU) 8-1500 Sandhill Dr., Ancaster, ON L9G 4V5 (Canada)		
PHONE: EMERGENCY PHONE:	42A Crimea Street, C/O A03886, Parramatta, NSW, 2150 (Australia) (508) 477-2264 (800) 424-9300 (USA and Canada 24/7 CHEMTREC) +44 20 3868 7152 (UK and EU 24/7) +61 2 8607 7057 (Australia 24/7)		
REVISION DATE: REVISION NUMBER: REVISED BY:	2024/11/11 2.8 Chip Quik Product Safety		
PRODUCT USE:	Soldering components for bonding semiconductor chips and packages to circuit boards.		
2. HAZARD IDENTIFICA	ΤΙΟΝ		
Classified in accordance with	European CLP Regulation 1272/2008		
CHEMICAL NAME:	4* H302 4* H312 4 H332 2A H319 2 H315 1 H317 1 H400 1 H410 1 H360FD H362 2 H351 ty (STOT) – Single Exposure (SE) Respiratory Tract Irritation 3 H335		
CHEMICAL FAMILY: CHEMICAL FORMULA:	Mixture Proprietary		
ROUTES OF ENTRY:	Inhalation, Ingestion, Skin/Eye Contact		
TARGET ORGANS:	Blood, Kidneys, Skin, Respiratory System, Nasal, Septum, Liver, Eyes		





Signal Word: Danger

GHS/CLP LABEL ELEMENTS:

LEAD WARNING

Hazard statement(s) H302 H312

Harmful if swallowed. Harmful in contact with skin.

H315 H317 H319 H332 H335 H351 H361	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child.
H362	May cause harm to breast-fed children.
H410	Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202 P233	Do not handle until all safety precautions have been read and understood. Keep container tightly closed.
P260	Do not breathe dust/fume/gas/mist/vapor/spray.
P262	Do not get in eyes, on skin, or on clothing.
P263	Avoid contact during pregnancy and while nursing.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink, or smoke when using this product.
P271	Use in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	In case of inadequate ventilation wear respiratory protection.
P301/P330/P331/P310 P303/P361/P352/P333/P313	IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER/Doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with soap & water. Get medical advice/attention if
	skin irritation or rash occurs or if you feel unwell.
P304/P340/312	IF INHALED: Remove victim to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
P305/P351/338/ P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call POISON CENTER/Doctor.
P308/P313	IF EXPOSED OR CONCERNED: Get medical advice/attention.
P342/P311	IF EXPERIENCING RESPIRATORY SYMPTOMS: Call POISON CENTER/Doctor.
P362	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P402/P404	Store in a dry place. Store in a closed container.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

POTENTIAL HEALTH EFFECTS (CHRONIC and OVEREXPOSURE)

Tin: Dust or fumes may cause irritation of the skin mucous membranes and may result in a benign Pneumoconiosis (Stannosis).

Silver: May cause discoloration of eyes and skin (Argyia).

Bismuth: May cause foul breath, a blue-black line on the gums, and Stomatitis.

Indium: May cause weight loss, pulmonary edema, blood damage and degenerative changes in liver and kidneys.

CHRONIC / ACUTE HEALTH HAZARDS

Lead: Women of child-bearing age should avoid exposure to lead and its inorganic compounds due to post-natal effects. Lead can cause potential injury to a developing fetus and possible effects on reproduction. Exposure to high levels of airborne or ingested lead may produce symptoms of anemia, weakness, constipation, nausea, and abdominal pain. Prolonged exposure may result in kidney and/or nervous system involvement.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE: Diseases of the blood-forming organs, kidneys, nervous and possibly reproductive systems. Occupational Asthma.

SECTION 2 NOTES:

Chip Quik Inc. does not recommend, manufacture, market, or endorse any of its products for human consumption.

Chronic Toxicity-Proposition 65, State of California: A WARNING! This product can expose you to Lead, which is known to the State of California to cause Cancer, Birth Defects, or other Reproductive Harm. For more information, go to www.P65Warnings.ca.gov. Federal and State Laws prohibit the use of lead solder in making joints in any private or public potable (drinking) water supply system. Breathing fumes may cause respiratory system irritation or damage. After handling solder, wash hands with soap and water before eating or smoking.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Classified in accordance with European CLP Regulation 1272/2008

Hazardous Ingredients (1)	C.A.S. Number	Weight Percent	OSHA PEL mg/m ³	ACGIH TLV TWA mg/m ³	LD 50 Ingested g/Kg	LD 50 Inhaled g/m ³
*+Lead	7439-92-1	Product contains	0.05	0.05	NE	ŇE
Tin	7440-31-5	one or more of	2.00	2.00	NE	NE
Silver	7440-22-4	these metallic	0.01	0.10	NE	NE
Bismuth	7440-69-9	elements in	NE	NE	NE	NE
Indium	7440-74-6	varying	NE	0.10	NE	NE
Copper	7440-50-8	percentages	1.00	1.00	NE	NE

SECTION 3 NOTES:

* denotes a chemical that is also listed in 29CFR 1910.1200(D) #4 as a known or suspected cancer hazard.

+ denotes a chemical regulated as toxic by the Environmental Protection Agency (EPA) as outlined in 40CFR Part 372 (section 313).

Percentages of individual components are not listed as this information is considered a trade secret.

(1) Per 29 CFR 1910 the mixture has not been tested as a whole. All hazardous components, which comprise 1% of the mixture (0.1% carcinogenic), are listed.

4. FIRST-AID MEASURES

Signs and symptoms of exposure: Inhalation-Nose and throat irritation, headache, dizziness, difficulty breathing, coughing. Ingestion-nausea, vomiting, cramps. Skin-redness, burning, rash, dryness. Eye-redness, burning, tearing, blurred vision.

Emergency first aid procedures:

EYES: Flush with plenty of water, contact a physician. If contact lenses can be removed easily, flush eyes without contact lenses.

SKIN: Wash affected area with plenty of warm, soapy water. If irritation persists, seek medical attention.

INGESTION: Call a physician or Poison Control Center immediately. Do not induce vomiting. Drink large amounts of water. Never give anything by mouth to an unconscious person

INHALATION: Remove to fresh air. Support respiration if required. If not breathing, seek immediate medical attention.

OTHER: Lead: Excessive overexposure may result in an acute or chronic illness. If symptoms are present, the individual should be immediately removed from exposure and a physician consulted.

5. FIREFIGHTING MEASURES

EXTINGUISHING MEDIA:	Dry chemical, foam
SPECIAL FIRE FIGHTING PROCEDURES:	Do not use water. Use NIOSH-approved self-contained Breathing Apparatus and full protective clothing if involved in a fire.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	May release Toxic metal and oxide fumes. High concentrations of dust may present explosion hazard. Water trapped below molten metal may explode thus spattering molten metal.
HAZARDOUS DECOMPOSITION PRODUCTS:	Lead oxide fumes and/or Lead particulate may be evolved.

SECTION 5 NOTES:

Molten solder alloys consisting of Bismuth, Copper, Indium, Lead, Silver, and/or Tin do not produce significant quantities of fumes below 900° F.

6. ACCIDENTAL RELEASE MEASURES

PRECAUTIONS AND EQUIPMENT: Material is extremely thick and will not flow out.

ACCIDENTAL RELEASE MEASURES: If material spills or leaks use a spatula to collect and place it in a plastic or glass jar. Remove traces of residue using cloth rags or paper towels moistened with Isopropyl Alcohol. Exposure to spilled material may be irritating. Follow on-site personal protective equipment recommendations.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Collect spillage.

SECTION 6 NOTES:

See Sections 2, 4, and 7 for additional information.

7. HANDLING AND STORAGE

HANDLING/STORAGE: Keep containers tightly closed when not in use. Use care to avoid spills. Avoid inhalation of fumes or dust. Avoid contact with eyes, skin, and clothing. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Wear appropriate personal protective equipment when working with or handling. Always wash hands thoroughly after handling this product. Dispose of following Federal, State/Provincial, and Local regulations.

OTHER PRECAUTIONS: Empty containers may retain product residues in vapor, liquid, and/or solid form. All labeled hazard precautions should be observed.

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in work areas. Always wash hands after handling material and before applying or using cosmetics/food/drink/tobacco.

SECTION 7 NOTES: Keep out of reach of children. Not for internal consumption.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limit Values:

Extraction is necessary to remove fumes evolved during reflow.

Also see section 3.

ENGINEERING CONTROLS: Use only with production equipment designed for use with solder.

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLVs.

RESPIRATORY PROTECTION: A (US: NIOSH; EU: EN 140:1998, EN 14387:2004 A)-approved air-purifying respirator with fume/organic chemical cartridge should be worn when airborne concentrations may be exceeded. General and local exhaust ventilation is the preferred means of protection.

EYE PROTECTION: Use with appropriate eye protection: Goggles or face shield (EU: EN 166-S 3 9).

SKIN PROTECTION: Protective gloves should be worn when the possibility of skin contact exists (EU: EN 374-1:2003).

PROTECTIVE CLOTHING OR EQUIPMENT: Work clothes should be worn and laundered in accordance with current Lead (Pb) standards (US: OSHA).

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in areas where solder products may be used. Always wash hands after handling soldering products and before applying or using cosmetics/food/drink/tobacco.

OTHER: Maintain eye wash stations in work areas. Avoid the use of contact lenses in high fume areas. Clean protective equipment regularly. Clean up spills immediately.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.2 Other Information

9.2.1 Information with regard to physical hazard classes No additional information available.
9.2.2 Other safety characteristics No additional information available.

SECTION 9 NOTES:

Other physical and chemical properties depend on alloy composition.

10. STABILITY AND REACTIVITY

STABILITY: CONDITIONS TO AVOID (STABILITY): INCOMPATIBILITY (MATERIAL TO AVOID): HAZARDOUS DECOMPOSITION/BY-PRODUCTS:

NE Oxidizing materials, acids, hydrogen peroxide, bases Harmful organic fumes and toxic oxide fumes may form at elevated temperatures. Lead oxide fumes and/or Lead particulate may be evolved. NE

POSSIBILITY OF HAZARDOUS REACTIONS: 11. TOXICOLOGICAL INFORMATION

INHALATION:

This product does not present a risk at ambient temperatures. The flux fumes evolved during soldering will irritate the nose, throat and lungs. Repeated or prolonged exposure to flux fumes may cause an allergic affect which may lead to occupational asthma.

Stable

SKIN:

Contact with flux fumes and flux residues may cause irritation and sensitization.

EYES:

Flux fumes may cause irritation.

Health Hazards (acute and chronic): Contact with dust and fumes may cause skin, eye and respiratory irritation. Ingestion and/or inhalation of material or fumes may result in flu like symptoms, insomnia, muscle weakness, nausea and abdominal pain. Gross inhalation or ingestion may be toxic and can result in death. Symptoms of toxicity may take hours or days to manifest. Chronic exposures, inhalation and ingestion, may result in kidney, red blood cell, reproductive and nervous system effects. Health effects may be cumulative over many exposures. Studies show that health risks vary by individual. Minimize exposure as a precaution. See OSHA 29CFR 1910.1025(subpart Z) for more information.

ACUTE TOXICITY:

Product/Ingredient Name Result	Species	Dose	Exposure
--------------------------------	---------	------	----------

SKIN CORRISION/IRRITATION: SERIOUS EYE DAMAGE/IRRITATI RESPIRATORY OR SKIN SENSITIZ GERM CELL MUTAGENICITY: CARCINOGENICITY:	•	NE Not available NE Not available		
OSHA: NA	ACGIH: Le	ead (Pb)-A3	NTP: NA	IARC: Lead (PB)-Group 2B
REPRODUCTIVE TOXICITY: STOT-SINGLE EXPOSURE:		Not available		
Product/Ingredient Name	Category		Route of exposure	Target organs
STOT-REPEATED EXPOSURE: ASPIRATION HAZARD:		Not available Not available		
11.2 Information on other hazards 11.2.1 Endocrine disrupting prope	-			

Not available.

11.2.2 Other information:

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named manufacturer, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

SECTION 11 NOTES:

This product has not been tested as a whole to determine its hazards. Synergistic or additive effects of the above chemicals are unknown, as are the effects of exposure to these chemicals in addition to others present in the work place. See Section 2 for additional health hazards.

12. ECOLOGICAL INFORMATION

TOXICITY:

Product/Ingredient Name	Result	Species	Exposure
Lead	Acute EC50 105 ppb Marine water	Algae - Chaetoceros sp Exponential growth phase	72 hours
	Acute EC50 0.489 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 8000 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute LC50 530 µg/l Fresh water	Crustaceans - Ceriodaphnia reticulata	48 hours
	Acute LC50 4400 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.44 ppm Fresh water	Fish - Cyprinus carpio - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 0.25 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.03 µg/l Fresh water	Fish - Cyprinus carpio	4 weeks

PERSISTENCE AND DEGRADIBILITY: NE

DIGAGOUNDERTIVET OTENTIAE.				
Product/Ingredient Name	LogPow	BCF	Potential	
MOBILITY IN SOIL:	NE			

RESULT OF PBT and vPvB ASSESSMENT: 12.6 Endocrine Disrupting Properties: 12.7 OTHER ADVERSE EFFECTS:

Not applicable Not available

No known significant effects or critical hazards

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Scrap and waste should be recycled or stored in a dry, sealed container for later disposal. Disposal must be in accordance with Federal, State/Provincial, and Local Regulations.

OTHER PRECAUTIONS: Avoid skin & eye contact, inhalation & ingestion of fumes and material. Wash contaminated clothing before reuse. Keep away from children.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

TRANSPORT HAZARD CLASSES: US DOT Hazardous Material Classification: Water Transportation: IATA Hazardous Material Classification:

Non-Hazardous Non-Hazardous Non-Hazardous

Not available Not available Not applicable None

15. REGULATORY INFORMATION

United States Regulatory Information:	
TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act (TSCA) Inventory.
TSCA 12 (b) Export Notification:	Not required.
Canada Regulatory Information:	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
U.S. FEDERAL REGULATIONS:	Not regulated
STATE REGULATIONS:	Not regulated
INTERNATIONAL REGULATIONS:	Not regulated
AUSTRALIAN REGULATIONS:	Not regulated
This product contains components known to the state of	of California to cause cancer or reproductive harm.
16. OTHER INFORMATION	

Not regulated

Not regulated

Not regulated

LEGEND: ACGIH American Conference of Governmental Industrial Hygienists ADG Australian Dangerous Goods Code European Agreement concerning the International Carriage of Dangerous Goods by Road ADR Australian Inventory of Chemical Substances AICS BCF Bioconcentration factor **Chemical Abstract Service** C.A.S. Classification, Labeling and Packaging CLP Department of Transportation DOT EC Effective Concentration **Environmental Protection Agency** EPA GHS Global Harmonized System Hazardous Material Identification System HMIS IARC International Agency for Research on Cancer International Air Transport Association ΙΑΤΑ IMDG International Maritime Dangerous Goods Code Lethal Concentration LC LD Lethal Dose NA Not available NE Not established NIOSH National Institute for Occupational Safety & Health NOEC No observed effective concentration NOHSC National Occupational Health and Safety Commission (Australia) National Toxicology Program NTP Occupational Safety and Health Administration OSHA PEL Permissible Exposure Limit Octanol water partition coefficient \mathbf{P}_{ow} Safety Data Sheet SDS Short-Term Exposure Limit STEL Specific target organ toxicity STOT Threshold Limit Value TLV TSCA **Toxic Substance Control Act** TWA: Time Weighted Average US DOT: United States Department of Transportation

PREPARATION INFORMATION:

This update supersedes all previously released documents.

DISCLAIMER:

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to Chip Quik at the time of issue. No warranty, guarantee, or representation is made by Chip Quik nor does Chip Quik assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances. The data on this Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet as a source for hazard information.

Copyright © 1994-2024 Chip Quik® Inc.