

Safety Data Sheet (SDS)

www.chipquik.com

To comply with European CLP Regulation 1272/2008, US 29CFR 1910.1200 OSHA's Hazard Communication Standard, and Australian NOHSC: 1008 [2004] and ADG Code 7.4

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Chip Quik Flux Remover: COSOLV175
SYNONYMS:
PART NUMBERS: COSOLV175-1L, COSOLV175-5GAL, COSOLV175-55GAL, COSOLV175-1.0

MANUFACTURER: Chip Quik Inc.
ADDRESS: 931-3909 Witmer Rd., Niagara Falls, NY 14305 (USA)
 3rd Floor, 207 Regent Street, London W1B 3HH (UK and EU)
 8-1500 Sandhill Dr., Ancaster, ON L9G 4V5 (Canada)
 42A Crimea Street, C/O A03886, Parramatta, NSW, 2150 (Australia)
PHONE: (508) 477-2264
EMERGENCY PHONE: (800) 424-9300 (USA and Canada 24/7 CHEMTREC)
 +44 20 3868 7152 (UK and EU 24/7)
 +61 2 8607 7057 (Australia 24/7)

REVISION DATE: 2022/07/22
REVISION NUMBER: 1.5
REVISED BY: Chip Quik Product Safety

PRODUCT USE: Removing flux from circuit boards.

2. HAZARD IDENTIFICATION

Classified in accordance with European CLP Regulation 1272/2008

Aspiration Hazard	1
Acute Toxicity	4
Skin Irritant	2
Skin Sensitization	1
Eye Irritation	2

CHEMICAL NAME: NA
CHEMICAL FAMILY: Mixture
CHEMICAL FORMULA: Proprietary

ROUTES OF ENTRY: Inhalation, Ingestion, Skin/Eye Contact

TARGET ORGANS: NA

GHS/CLP:



Signal Word: Danger

GHS/CLP LABEL ELEMENTS:

Hazard statement(s)
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.

Precautionary statement(s)
 P102 Keep out of reach of children.
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P233 Keep container tightly closed.
 P260 Do not breathe dust/fume/gas/mist/vapor/spray.
 P262 Do not get in eyes, on skin, or on clothing.
 P264 Wash hands thoroughly after handling.

P270	Do not eat, drink, or smoke when using this product.
P271	Use in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	In case of inadequate ventilation wear respiratory protection.
P301/P330/P331/P310	IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER/Doctor.
P303/P361/P352/P333/P313	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with soap & water. Get medical advice/attention if skin irritation or rash occurs or if you feel unwell.
P304/P340/312	IF INHALED: Remove victim to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
P305/P351/338/P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call POISON CENTER/Doctor.
P308/P313	IF EXPOSED OR CONCERNED: Get medical advice/attention.
P342/P311	IF EXPERIENCING RESPIRATORY SYMPTOMS: Call POISON CENTER/Doctor.
P362	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P402/P404	Store in a dry place. Store in a closed container.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT:	May cause moderate irritation. Do not allow material to come in contact with eyes.
SKIN CONTACT:	May cause moderate skin irritation.
INHALATION:	May cause irritation to the respiratory tract.
INGESTION:	Harmful if swallowed. May cause irritation to the mouth, throat, and stomach. May cause abdominal discomfort, nausea, vomiting, and/or diarrhea.
CHRONIC:	Not established.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE: Diseases of the blood-forming organs, kidneys, nervous and possibly reproductive systems. Occupational Asthma.

SECTION 2 NOTES:

Chip Quik Inc. does not recommend, manufacture, market, or endorse any of its products for human consumption.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Classified in accordance with European CLP Regulation 1272/2008

Hazardous Ingredients ⁽¹⁾	C.A.S. Number	Weight Percent	OSHA PEL mg/m ³	ACGIH TLV TWA mg/m ³	LD 50 Ingested g/Kg	LD 50 Inhaled g/m ³
Hydrocarbons	64742-47-8	<60	NE	NE	NE	NE
2-methylpentane-2,4-diol	107-41-5	<20	NE	NE	NE	NE
Carboxyl-phosphate-ester	-	<20	NE	NE	NE	NE
Propanol	34590-94-8	<20	NE	NE	NE	NE

SECTION 3 NOTES:

(1) Per 29 CFR 1910 the mixture has not been tested as a whole. All hazardous components, which comprise 1% of the mixture (0.1% carcinogenic), are listed. Percentages of individual components are not listed as this information is considered a trade secret.

4. FIRST-AID MEASURES

EYES: Flush with plenty of water, contact a physician. If contact lenses can be removed easily, flush eyes without contact lenses.

SKIN: Wash affected area with plenty of warm, soapy water. If irritation persists, seek medical attention.

INGESTION: Call a physician or Poison Control Center immediately. Do not induce vomiting.

INHALATION: Remove to fresh air. If not breathing, seek immediate medical attention.

5. FIREFIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam

SPECIAL FIRE FIGHTING PROCEDURES: Use NIOSH-approved self-contained Breathing Apparatus and full protective clothing if involved in a fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Not classified as flammable, but may present a risk in the event of a fire. Explosive vapor/air mixtures may be formed. Under high temperatures (fire) toxic vapors are released (CO, CO₂).

6. ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: If material spills or leaks collect and place it in a plastic or glass jar. Remove traces of residue using cloth rags or paper towels. Exposure to spilled material may be irritating. Follow on-site personal protective equipment recommendations.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Collect spillage.

SECTION 6 NOTES:

See Sections 2, 4, and 7 for additional information.

7. HANDLING AND STORAGE

HANDLING/STORAGE: Keep containers tightly closed when not in use. Use care to avoid spills. Avoid inhalation of fumes or dust. Avoid contact with eyes, skin, and clothing. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Wear appropriate personal protective equipment when working with or handling. Always wash hands thoroughly after handling this product. Dispose of following Federal, State/Provincial, and Local regulations.

OTHER PRECAUTIONS: Empty containers may retain product residues in vapor, liquid, and/or solid form. All labeled hazard precautions should be observed.

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in work areas. Always wash hands after handling material and before applying or using cosmetics/food/drink/tobacco.

SECTION 7 NOTES:

Keep out of reach of children.
Not for internal consumption.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limit Values:

	Country	mg/m ³	ppm
2-methylpentane-2,4-diol	USA (NIOSH)	125 (STEL 15min)	25 (STEL 15min)
	United Kingdom	123 (TWA 8hr/15min)	25 (TWA 8hr/15min)
	France	125 (TWA 15min)	25 (TWA 15min)
	Germany	49 (TWA 8hr), 98 (STEL 15min)	10 (TWA 8hr), 20 (STEL 15min)
	Belgium	123 (TWA 8hr)	25 (TWA 8hr)
	Switzerland	49 (TWA 8hr), 98 (STEL 15min)	10 (TWA 8hr), 20 (STEL 15min)
Propanol	USA (NIOSH)	600 (TWA 8hr)	100 (TWA 8hr)
	EU	300 (TWA 8hr), 300 (STEL 15min)	50 (TWA 8hr), 50 (STEL 15min)

Also see section 3.

ENGINEERING CONTROLS: Use only with production equipment designed for use with flux remover.

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLVs.

RESPIRATORY PROTECTION: Use with adequate ventilation.

EYE PROTECTION: Use with appropriate safety glasses.

SKIN PROTECTION: Protective gloves.

PROTECTIVE CLOTHING OR EQUIPMENT: Work clothes should be worn and laundered in accordance with current OSHA Lead (Pb) standards.

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in areas where solder products may be used. Always wash hands after handling soldering products and before applying or using cosmetics/food/drink/tobacco.

OTHER: Maintain eye wash stations in work areas. Avoid the use of contact lenses in high fume areas. Clean protective equipment regularly. Clean up spills immediately.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Clear liquid
ODOR:	Odorless
ODOR THRESHOLD:	NE
pH as SUPPLIED:	N/A
MELTING POINT:	NE
FREEZING POINT:	NE
INITIAL BOILING POINT:	NE
BOILING RANGE:	175-215°C
FLASH POINT:	77°C
EVAPORATION RATE:	NE
FLAMMABILITY (solid):	NE
UPPER/LOWER FLAMMABILITY:	NE
UPPER/LOWER EXPLOSIVE LIMITS:	NE
VAPOR PRESSURE (mmHg):	N/A
VAPOR DENSITY (AIR = 1):	N/A
RELATIVE DENSITY:	NE
SOLUBILITY IN WATER:	Not Miscible
PARTITION COEFFICIENT (n-octanol/water):	NE
AUTOIGNITION TEMPERATURE:	NE
DECOMPOSITION TEMPERATURE:	NE
VISCOSITY:	N/A

10. STABILITY AND REACTIVITY

STABILITY: Stable
CONDITIONS TO AVOID (STABILITY): NE
INCOMPATIBILITY (MATERIAL TO AVOID): Oxidizing materials, acids, hydrogen peroxide, bases
HAZARDOUS DECOMPOSITION/BY-PRODUCTS: Harmful organic fumes and toxic oxide fumes may form at elevated temperatures. CO and CO₂.
POSSIBILITY OF HAZARDOUS REACTIONS: NE

11. TOXICOLOGICAL INFORMATION

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

2-methylpentane-2,4-diol (107-41-5)
 Oral LD50 Rat 4000 mg/kg
 Dermal LD50 Rabbit 13000 mg/kg

Propanol (34590-94-8)
 Oral LD50 Rat 5000 mg/kg
 Dermal LD50 Rabbit 9510 mg/kg
 Inhalation LC50 Rat 55 ppm 4 h

Component Carcinogenicity

Hydrocarbons (64742-47-8)

INHALATION:

This product does not present a risk at ambient temperatures. The flux remover fumes evolved during soldering will irritate the nose, throat and lungs. Repeated or prolonged exposure to flux remover fumes may cause an allergic affect which may lead to occupational asthma.

SKIN:

Contact with flux remover fumes and flux remover residues may cause irritation and sensitization.

EYES:

Flux remover fumes may cause irritation.

ACUTE TOXICITY: Not available
SKIN CORRISSION/IRRITATION: Not available
SERIOUS EYE DAMAGE/IRRITATION: Not available
RESPIRATORY OR SKIN SENSITIZATION: NE
GERM CELL MUTAGENICITY: Not available
CARCINOGENICITY: Not available
REPRODUCTIVE TOXICITY: Not available
STOT-SINGLE EXPOSURE: Not available
STOT-REPEATED EXPOSURE: NE
ASPIRATION HAZARD: May be fatal if swallowed and enters airways

12. ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity:

2-methylpentane-2,4-diol	107-41-5
Fish	LC50 96 h Pimephales promelas 10000 mg/L [flow-through]
Algae	EC50 72 h Selenastrum capricornutum >1000 mg/L IUCLID
Invertebrate	EC50 48 h Daphnia magna 1919 mg/L IUCLID

TOXICITY: Not available
PERSISTENCE AND DEGRADIBILITY: NE
BIOACCUMULATIVE POTENTIAL: Not available
MOBILITY IN SOIL: NE
RESULT OF PBT and vPvB ASSESSMENT: Not applicable
OTHER ADVERSE EFFECTS: NE

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Scrap and waste should be recycled or stored in a dry, sealed container for later disposal. Disposal must be in accordance with Federal, State/Provincial, and Local Regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

UN Number: Not available
UN Proper Shipping Name: Not available
Packaging Group: Not applicable
Environmental Hazards: None

TRANSPORT HAZARD CLASSES:

US DOT Hazardous Material Classification: Non-Hazardous
 Water Transportation: Non-Hazardous
 IATA Hazardous Material Classification: Non-Hazardous
 ADR Road Regulations: Not regulated
 IMDG Sea Regulations: Not regulated

15. REGULATORY INFORMATION

All ingredients used to manufacture this product are listed on the EPA TSCA Inventory. Finished product is not listed on the EPA TSCA Inventory.

U.S. FEDERAL REGULATIONS:	Not regulated
STATE REGULATIONS:	Not regulated
INTERNATIONAL REGULATIONS:	Not regulated
AUSTRALIAN REGULATIONS:	Not regulated

16. OTHER INFORMATION**LEGEND:**

ACGIH	American Conference of Governmental Industrial Hygienists
ADG	Australian Dangerous Goods Code
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AICS	Australian Inventory of Chemical Substances
BCF	Bioconcentration factor
C.A.S.	Chemical Abstract Service
CLP	Classification, Labeling and Packaging
DOT	Department of Transportation
EC	Effective Concentration
EPA	Environmental Protection Agency
GHS	Global Harmonized System
HMIS	Hazardous Material Identification System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods Code
LC	Lethal Concentration
LD	Lethal Dose
NA	Not available
NE	Not established
NIOSH	National Institute for Occupational Safety & Health
NOEC	No observed effective concentration
NOHSC	National Occupational Health and Safety Commission (Australia)
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
P_{ow}	Octanol water partition coefficient
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
STOT	Specific target organ toxicity
TLV	Threshold Limit Value
TSCA	Toxic Substance Control Act
TWA:	Time Weighted Average
US DOT:	United States Department of Transportation

PREPARATION INFORMATION:

This update supersedes all previously released documents.

DISCLAIMER:

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to Chip Quik at the time of issue. No warranty, guarantee, or representation is made by Chip Quik nor does Chip Quik assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances. The data on this Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet as a source for hazard information.