# **CHIPQUIK®**

## **Potting Compound**

### Safety Data Sheet (SDS)

www.chipquik.com

To comply with European CLP Regulation 1272/2008, US 29CFR 1910.1200 OSHA's Hazard Communication Standard, and Australian NOHSC: 1008 [2004] and ADG Code 7.4

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Chip Quik Two-Part Potting Compound (Re-Enterable): CQ9000

**SYNONYMS:** Potting Compound

PART NUMBERS: CQ9000-100, CQ9000-200, CQ9000-400

MANUFACTURER: Chip Quik Inc.

ADDRESS: 931-3909 Witmer Rd., Niagara Falls, NY 14305 (USA)

3rd Floor, 207 Regent Street, London W1B 3HH (UK and EU)

8-1500 Sandhill Dr., Ancaster, ON L9G 4V5 (Canada)

42A Crimea Street, C/O A03886, Parramatta, NSW, 2150 (Australia)

**PHONE**: (508) 477-2264

EMERGENCY PHONE: (800) 424-9300 (USA and Canada 24/7 CHEMTREC)

+44 20 3868 7152 (UK and EU 24/7) +61 2 8607 7057 (Australia 24/7)

**REVISION DATE:** 2021/09/16

REVISION NUMBER: 1.1

REVISED BY: Chip Quik Product Safety

**PRODUCT USE:** Potting and encapsulating electronics inside cases, cables, and splices.

#### 2. HAZARD IDENTIFICATION

Classified in accordance with European CLP Regulation 1272/2008

Respiratory Sensitizer 1
Skin Sensitizer 1A
Reproductive Toxicity 1B

CHEMICAL NAME: NA
CHEMICAL FAMILY: Mixture
CHEMICAL FORMULA: Proprietary

ROUTES OF ENTRY: Inhalation, Ingestion, Skin/Eye Contact

TARGET ORGANS: NA





Signal Word: Danger

#### GHS/CLP LABEL ELEMENTS:

#### Hazard statement(s)

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

Precautionary statement(s)

P102 Keep out of reach of children.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P233 Keep container tightly closed.

P260 Do not breathe dust/fume/gas/mist/vapor/spray.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash hands thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P271 Use in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 In case of inadequate ventilation wear respiratory protection.

P301/P330/P331/P310 IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER/Doctor.

P303/P361/P352/P333/P313 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with soap & water. Get medical advice/attention if

skin irritation or rash occurs or if you feel unwell.

P304/P340/312 IF INHALED: Remove victim to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if

you feel unwell.

P305/P351/338/P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call POISON CENTER/Doctor.

P308/P313 IF EXPOSED OR CONCERNED: Get medical advice/attention.

P342/P311 IF EXPERIENCING RESPIRATORY SYMPTOMS: Call POISON CENTER/Doctor.

P362 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P402/P404 Store in a dry place. Store in a closed container.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### **POTENTIAL HEALTH EFFECTS:**

**EYE CONTACT:** May cause moderate irritation. Do not allow material to come in contact with eyes.

**SKIN CONTACT:** May cause moderate skin irritation. **INHALATION:** May cause irritation to the respiratory tract.

INGESTION: Harmful if swallowed. May cause irritation to the mouth, throat, and stomach. May cause abdominal discomfort, nausea,

vomiting, and/or diarrhea.

CHRONIC: Not established.

**MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE:** Diseases of the blood-forming organs, kidneys, nervous and possibly reproductive systems. Occupational Asthma.

#### **SECTION 2 NOTES:**

Chip Quik Inc. does not recommend, manufacture, market, or endorse any of its products for human consumption.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

#### Classified in accordance with European CLP Regulation 1272/2008

Hazardous Ingredients (1)	C.A.S. Number	Weight Percent	OSHA PEL mg/m <sup>3</sup>	ACGIH TLV TWA mg/m <sup>3</sup>	LD 50 Ingested g/Kg	LD 50 Inhaled g/m <sup>3</sup>
Soybean Oil	8001-22-7	<67	NE	NE	NE	NE
Copolymer	25655-35-0	<28	NE	NE	NE	NE
Epoxidized Vegetable Oil	8013-07-8	<8	NE	NE	NE	NE
Toluene	108-88-3	<0.3	NE	NE	NE	NE
Maleic Anhydride	108-31-6	<0.3	NE	NE	NE	NE
Hydrotreated heavy naphthenic petroleum distillates	64742-52-5	<75	NE	NE	NE	NE
1,3-Butadiene, homopolymer, hydroxy- terminated	69102-90-5	<30	NE	NE	NE	NE
Methyldidecylamine	7396-58-9	<10	NE	NE	NE	NE

#### **SECTION 3 NOTES:**

(1) Per 29 CFR 1910 the mixture has not been tested as a whole. All hazardous components, which comprise 1% of the mixture (0.1% carcinogenic), are listed. Percentages of individual components are not listed as this information is considered a trade secret.

#### 4. FIRST-AID MEASURES

#### Emergency first aid procedures:

EYES: Flush with plenty of water, contact a physician. If contact lenses can be removed easily, flush eyes without contact lenses.

SKIN: Wash affected area with plenty of warm, soapy water. If irritation persists, seek medical attention.

INGESTION: Call a physician or Poison Control Center immediately. Never give anything by mouth to an unconscious person

INHALATION: Remove to fresh air. Support respiration if required. If not breathing, seek immediate medical attention.

5. FIREFIGHTING MEASURES

**EXTINGUISHING MEDIA:** Dry chemical, foam

Alcohol-resistant foam Carbon Dioxide (CO2)

Water Spray

SPECIAL FIRE FIGHTING PROCEDURES: Use NIOSH-approved self-contained Breathing Apparatus and full protective clothing if involved in a fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: May release toxic oxides, carbon oxides, silicon oxides and formaldehyde.

#### 6. ACCIDENTAL RELEASE MEASURES

PRECAUTIONS AND EQUIPMENT: Material is extremely thick and will not flow out.

**ACCIDENTAL RELEASE MEASURES:** If material spills or leaks use a spatula to collect and place it in a plastic or glass jar. Remove traces of residue using cloth rags or paper towels. Follow on-site personal protective equipment recommendations.

**ENVIRONMENTAL PRECAUTIONS:** Avoid release to the environment. Collect spillage.

#### SECTION 6 NOTES:

See Sections 2, 4, and 7 for additional information.

#### 7. HANDLING AND STORAGE

**HANDLING/STORAGE:** Keep containers tightly closed when not in use. Use care to avoid spills. Avoid inhalation of fumes or dust. Avoid contact with eyes, skin, and clothing. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Wear appropriate personal protective equipment when working with or handling. Always wash hands thoroughly after handling this product. Dispose of following Federal, State/Provincial, and Local regulations.

OTHER PRECAUTIONS: Empty containers may retain product residues in vapor, liquid, and/or solid form. All labeled hazard precautions should be observed

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in work areas. Always wash hands after handling material and before applying or using cosmetics/food/drink/tobacco.

#### **SECTION 7 NOTES:**

For industrial use only. Keep out of reach of children. Not for internal consumption.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Occupational Exposure Limits

Ingredient	CAS No.	Agency	Limit type	Comments
Maleic Anhydride	108-31-6	ACGIH	TWA (inhalable fraction and vapor):0.01 mg/m3;TWA:0.01 mg/m3	Sensitizer, A4: Not classified as a human carcinogen Dermal/Respiratory Sensitizer
Maleic Anhydride	108-31-6	OSHA	TWA:1 mg/m3(0.25 ppm)	
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not classified as a human carcinogen
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300	
			ppm	
Vegetable Oil Mist, Total Dust	8001-22-7	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance Name	End Use	Exposure Route	Potential Health Effects	Value
A I A				

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance Name	Environmental Compartment	Value
***		

Also see section 3.

ENGINEERING CONTROLS: Use only with production equipment designed for use with potting compound.

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLVs.

**RESPIRATORY PROTECTION:** A (US: NIOSH; EU: EN 140:1998, EN 14387:2004 A) approved air-purifying respirator with fume/organic chemical cartridge should be worn when airborne concentrations may be exceeded. General and local exhaust ventilation is the preferred means of protection.

EYE PROTECTION: Use with appropriate eye protection: Goggles or face shield (EU: EN 166-S 3 9).

SKIN PROTECTION: Protective gloves should be worn when the possibility of skin contact exists (EU: EN 374-1:2003).

PROTECTIVE CLOTHING OR EQUIPMENT: Work clothes should be worn and laundered in accordance with current standards (US: OSHA).

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in areas where solder products may be used. Always wash hands after handling soldering products and before applying or using cosmetics/food/drink/tobacco.

**OTHER:** Maintain eye wash stations in work areas. Avoid the use of contact lenses in high fume areas. Clean protective equipment regularly. Clean up spills immediately.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Liquid

ODOR: Mild hydrocarbon aroma

**ODOR THRESHOLD:** NE pH as SUPPLIED: NA **MELTING POINT:** NA FREEZING POINT: NA **INITIAL BOILING POINT:** NA **BOILING RANGE:** 246°C 300°C FLASH POINT: **EVAPORATION RATE:** NA FLAMMABILITY (solid): NE **UPPER/LOWER FLAMMABILITY:** NE **UPPER/LOWER EXPLOSIVE LIMITS:** NF VAPOR PRESSURE (mmHg): NA VAPOR DENSITY (AIR = 1): NA **RELATIVE DENSITY:** 0.89 **SOLUBILITY IN WATER:** NA PARTITION COEFFICIENT (n-octanol/water): ΝE **AUTOIGNITION TEMPERATURE:** NF

10. STABILITY AND REACTIVITY

**DECOMPOSITION TEMPERATURE:** 

VISCOSITY:

STABILITY: Stable under normal conditions

CONDITIONS TO AVOID (STABILITY): NE

INCOMPATIBILITY (MATERIAL TO AVOID): Oxidizing materials, acids, hydrogen peroxide, bases

NE

NA

HAZARDOUS DECOMPOSITION/BY-PRODUCTS: Harmful organic fumes and toxic oxide fumes may form at elevated temperatures.

Formaldehyde.

POSSIBILITY OF HAZARDOUS REACTIONS: Use at elevated temperatures may form highly hazardous compounds. Can react with strong

oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin Contact

Ingestion Eye Contact

ACUTE TOXICITY: NE
SKIN CORRISION/IRRITATION: NE
SERIOUS EYE DAMAGE/IRRITATION: NA
RESPIRATORY OR SKIN SENSITIZATION: NE
GERM CELL MUTAGENICITY: NA

CARCINOGENICITY:

OSHA: NA ACGIH: NA NTP: NA IARC: NA

#### REPRODUCTIVE TOXICITY:

Name	Route	Value	Species	Test Result	Exposure Duration
Toluene	Ingestion	Toxic to development	RAT	LOAEL 520 mg/kg/day	During gestation
Toluene	Inhalation	Toxic to development	Human	NA	Poisoning and/or abuse

STOT-SINGLE EXPOSURE: NA
STOT-REPEATED EXPOSURE: NA
ASPIRATION HAZARD:

Name Value
Toluene Aspiration Hazard

#### **SECTION 11 NOTES:**

This product has not been tested as a whole to determine its hazards. Synergistic or additive effects of the above chemicals are unknown, as are the effects of exposure to these chemicals in addition to others present in the work place. See Section 2 for additional health hazards.

#### 12. ECOLOGICAL INFORMATION

TOXICITY: NE PERSISTENCE AND DEGRADIBILITY: NE BIOACCUMULATIVE POTENTIAL:

Product/Ingredient Name	LoaPow	BCF	Potential

NA

MOBILITY IN SOIL: NE

RESULT OF PBT and vPvB ASSESSMENT: NA OTHER ADVERSE EFFECTS: NE

#### 13. DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHOD:** Scrap and waste should be recycled or stored in a dry, sealed container for later disposal. Disposal must be in accordance with Federal, State/Provincial, and Local Regulations.

OTHER PRECAUTIONS: Avoid skin & eye contact, inhalation & ingestion of fumes and material. Wash contaminated clothing before reuse. Keep away from children.

#### 14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

UN Number:
UN Proper Shipping Name:
Packaging Group:
Environmental Hazards:
Not available
Not applicable
None

#### TRANSPORT HAZARD CLASSES:

US DOT Hazardous Material Classification:
Water Transportation:
Non-Hazardous
Non-Hazardous
Non-Hazardous
Non-Hazardous
Non-Hazardous
Not regulated
MDG Sea Regulations
Not regulated
ADG Land Transportation
Not regulated

#### 15. REGULATORY INFORMATION

All ingredients used to manufacture this product are listed on the EPA TSCA Inventory. Finished product is not listed on the EPA TSCA Inventory.

U.S. FEDERAL REGULATIONS:Not regulatedSTATE REGULATIONS:Not regulatedINTERNATIONAL REGULATIONS:Not regulatedAUSTRALIAN REGULATIONS:Not regulated

#### 16. OTHER INFORMATION

LEGEND:

**ACGIH** American Conference of Governmental Industrial Hygienists

ADG Australian Dangerous Goods Code

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS Australian Inventory of Chemical Substances

BCF Bioconcentration factor C.A.S. Chemical Abstract Service

CLP Classification, Labeling and Packaging

DOT Department of Transportation EC Effective Concentration

EPA Environmental Protection Agency
GHS Global Harmonized System

HMIS
IARC
International Agency for Research on Cancer
IATA
International Air Transport Association
IMDG
International Maritime Dangerous Goods Code

LC Lethal Concentration
LD Lethal Dose

NA Not available
NE Not established

NIOSH National Institute for Occupational Safety & Health

NOEC No observed effective concentration

NOHSC National Occupational Health and Safety Commission (Australia)

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit
Pow Octanol water partition coefficient

SDS Safety Data Sheet

STEL Short-Term Exposure Limit
STOT Specific target organ toxicity
TLV Threshold Limit Value
TSCA Toxic Substance Control Act
TWA: Time Weighted Average

**US DOT:** United States Department of Transportation

#### PREPARATION INFORMATION:

This update supersedes all previously released documents.

#### **DISCLAIMER:**

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to Chip Quik at the time of issue. No warranty, guarantee, or representation is made by Chip Quik nor does Chip Quik assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances. The data on this Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet as a source for hazard information.

Copyright © 1994-2021 Chip Quik® Inc.